

AZURE

lighting solutions




ciana surface mounted downlight



SYDNEY
AUSTRALIA
WWW.AZURELIGHTINGSOLUTIONS.COM

Product Specifications



Power Consumption:	15W/20W/25W
Total luminous flux:	1440 lm/ 1920 lm/ 2400lm
Dimensions (LxWxH):	100x100x145mm
Beam Angle:	15°, 20°, 30°, 36°

General Specifications

Fixture Material:	Aluminium
Trim Finish:	White
Mounting:	Surface Mounted
LED Type:	Philips COB
Adjustability:	Fixed
Binning:	3 Step Macadam
Correlated Colour Temperature	2700K, 3000K, 3500K, 4000K
Colour Rendering Index:	>90
R9 Value:	>50
Light Distribution:	Symmetric
Ambient Operating Temperature:	-25° to 50°
Driver Input Voltage:	220-240VAC 50-60Hz
Control Gear:	Remote Tridonic or equivalent driver
Control Options:	Fixed Output, DALI, Push Dim, 0-10V, Casambi
Protection Class:	Class I
Lumen Maintenance:	L80 B10 90,000 Hours
IP Rating:	IP20
Warranty:	5-Year Limited
Standards:	CE, ROHS

Lumen values are based on CRI90 at CCT 4000K


All product specifications and data are subject to change without notice

A Z U R E


l i g h t i n g
s o l u t i o n s

Photometrics


15° BEAM ANGLE



24° BEAM ANGLE



36° BEAM ANGLE



Accessories



Honeycomb Louvre

A Z U R E

l i g h t i n g
s o l u t i o n s

Specifications Code

CIANA.100S. F . 15 . 20 . 930 . N . 15 . W

F=FIXED

15=15W
20=20W
25=25W

20=IP20

927=2700K
930=3000K
935=3500K
940=4000K

N=NON DIM
D=DALI
P=PUSH DIM
0=0-10V
C=CASAMBI
X=NO DRIVER

15=15°
24=24°
36=36°

W=WHITE

Accessories

+ 1 . H

1=BLACK
2=SPECULAR
3=WHITE

H=HONEYCOMB