

AZURE

lighting solutions

Track Mount



Recessed Mount



Surface Mount



MIRA SPOT LIGHTS






SYDNEY
AUSTRALIA

AZURELIGHTINGSOLUTIONS.COM.AU

Product Specifications

Track Mount



Product Name:	Mira.TR.50	Mira.TR.66	Mira.TR.80
Power Consumption:	7W	10-15W	20-30W
Total luminous flux:	Up to 735lm	Up to 1650lm	Up to 3780lm
Dimensions (DxH):	Ø50x144mm	Ø66x180mm	Ø80x180mm
Beam Angle:	15°, 20°, 30°	15°, 20°, 36°	20°, 24°, 30°, 36°

General Specifications




Fixture Material:	Aluminium
Trim Finish:	Black, White, Custom
Mounting:	Track
LED Type:	Citizen COB
Binning:	3 Step MacAdam
Correlated Colour Temperature	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, 6500K
Colour Rendering Index:	>90
R9 Value:	>50
Light Distribution:	Symmetric
Ambient Operating Temperature:	-25° to 50°
Driver Input Voltage:	220-240VAC 50-60Hz
Control Gear:	TCI
Control Options:	Fixed Output, DALI, Push Dim, 0-10V, Casambi
Protection Class:	Class II
Lumen Maintenance:	L80 B10 60,000 Hours
IP Rating:	IP20
Warranty:	7 Years

Lumen values are based on CRI90 at CCT 4000K

All product specifications and data are subject to change without notice

Product Specifications

Recessed Mount



Product Name:	Mira.REC.50	Mira.REC.66	Mira.REC.80
Power Consumption:	7W	10-15W	20-30W
Total luminous flux:	Up to 735lm	Up to 1650lm	Up to 3780lm
Dimensions (DxH):	Ø50x144mm	Ø66x180mm	Ø80x180mm
Beam Angle:	15°, 20°, 30°	15°, 20°, 36°	20°, 24°, 30°, 36°

General Specifications




Fixture Material:	Aluminium
Trim Finish:	Black, White, Custom
Mounting:	Recessed
LED Type:	Citizen COB
Binning:	3 Step MacAdam
Correlated Colour Temperature	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, 6500K
Colour Rendering Index:	>90
R9 Value:	>50
Light Distribution:	Symmetric
Ambient Operating Temperature:	-25° to 50°
Driver Input Voltage:	220-240VAC 50-60Hz
Control Gear:	TCI
Control Options:	Fixed Output, DALI, Push Dim, 0-10V, Casambi
Protection Class:	Class II
Lumen Maintenance:	L80 B10 60,000 Hours
IP Rating:	IP20
Warranty:	7 Years

Lumen values are based on CRI90 at CCT 4000K

All product specifications and data are subject to change without notice

Product Specifications

Surface Mount



Product Name:	Mira.SM.50	Mira.SM.66	Mira.SM.80
Power Consumption:	7W	10-15W	20-30W
Total luminous flux:	Up to 735lm	Up to 1650lm	Up to 3780lm
Dimensions (DxH):	Ø50x144mm	Ø66x180mm	Ø80x180mm
Beam Angle:	15°, 20°, 30°	15°, 20°, 36°	20°, 24°, 30°, 36°

General Specifications

Fixture Material:	Aluminium
Trim Finish:	Black, White, Custom
Mounting:	Surface
LED Type:	Citizen COB
Binning:	3 Step MacAdam
Correlated Colour Temperature	2700K, 3000K, 3500K, 4000K, 5000K, 6000K, 6500K
Colour Rendering Index:	>90
R9 Value:	>50
Light Distribution:	Symmetric
Ambient Operating Temperature:	-25° to 50°
Driver Input Voltage:	220-240VAC 50-60Hz
Control Gear:	TCI
Control Options:	Fixed Output, DALI, Push Dim, 0-10V, Casambi
Protection Class:	Class II
Lumen Maintenance:	L80 B10 60,000 Hours
IP Rating:	IP20
Warranty:	7 Years

Lumen values are based on CRI90 at CCT 4000K

All product specifications and data are subject to change without notice

Optical Accessories



Honeycomb Louvre

Track Accessories



3/4 Wire
Black Track Rail



3/4 Wire
White Track Rail



L Connector



Flexible Connector



I Connector



X Connector



T Connector



Suspension Kit

Colour Rendering Index

The Color Rendering Index (CRI) serves as a metric to gauge how accurately a light source portrays the colors of various objects in a given space. Originally comprised of 8 sample colors, the CRI has expanded to 15 samples to provide a more comprehensive evaluation. Notably, within these samples, R9 to R15 focus on assessing special colors with high chroma. Specifically, R9 evaluates the rendering of red tones, while R15 is dedicated to evaluating the portrayal of skin tones. This extension of color samples, coupled with attention to high-chroma colors, enhances the precision in evaluating a light source's ability to faithfully reproduce a diverse range of colors.





Fig 1 - Colour Rendering Index 4000K, CRI >95

TM30 Rf 92
Rg 100



IES TM-30

TM-30 is the Illuminating Engineering Society (IES) Method for Evaluating Light Source Color Rendition, is a standard developed by the IES to assess the color rendering properties of light sources. It provides a comprehensive set of metrics and values that go beyond the traditional color rendering index (CRI), offering a more detailed and accurate understanding of how well a light source renders colors.

Fig 2 -Colour Vector Graphic 4000K, CRI >90